



Temperature Ranges

Ranges, °F

| Models | K | A | B ADJ | E J ADJ | G GJ ADJ |
|-------------|----|------|----------|---------------|----------------|
| Dial Size | 1" | 1.5" | 2.25" | 3" | 5" |
| -150-1000°F | | | X | X | X |
| -150-700°F | | | X | X | X |
| -150-500°F | | | X | X | X |
| -120-100°F | | | | X | |
| -100-400°F | | | | X | |
| -100-200°F | | | | X | |
| -100-100°F | | | X | X | X |
| -70-230°F | | X | X | X | X |
| -65-50°F | | X | X | | |
| -50-300°F | | | X | X | X |
| -50-250°F | | | X | X | X |
| -50-125°F | | | X | X | |
| -40-120°F | | | X | X | X |
| -40-160°F | X | X | X | X | X |
| -20-180°F | | X | X | X | X |
| 0-800°F | | | X | X | X |
| 0-700°F | | | X | X | |
| 0-400°F | | | X | X | |
| 0-300°F | | | X | X | |
| 0-250°F | | X | X | X | X |
| 0-220°F | X | X | X | X | X |
| 0-200°F | | | X | X | X |
| 0-150°F | | X | X | X | X |
| 0-100°F | | | X | X | X |
| 20-240°F | | X | X | X | X |
| 25-125°F | | X | X | X | X |
| 50-650°F | X | | X | X | X |
| 50-500°F | X | X | X | X | X |
| 50-400°F | | | X | X | X |
| 50-300°F | X | X | X | X | X |
| 50-250°F | | X | X | X | X |
| 50-160°F | | X | X | | X |
| 100-200°F | | | | X | |
| 150-750°F | | X | X | X | X |
| 200-1000°F | | | X | X | X |

Ranges, °C

| Models | K | A | B ADJ | E J ADJ | G GJ ADJ |
|-----------|----|------|----------|---------------|----------------|
| Dial Size | 1" | 1.5" | 2.25" | 3" | 5" |
| -100-50°C | | | X | X | X |
| -75-325°C | | | | X | |
| -70-160°C | | | X | X | X |
| -70-25°C | | | X | X | X |
| -50-100°C | | X | X | X | X |
| -40-40°C | | | | X | |
| -30-30°C | X | | | X | |
| -10-200°C | | | X | | X |
| -10-110°C | X | X | X | X | X |
| 0-400°C | | | X | X | X |
| 0-300°C | | X | X | X | X |
| 0-250°C | | X | X | X | X |
| 0-200°C | | X | X | X | X |
| 0-150°C | X | X | X | | X |
| 0-100°C | | | X | X | X |
| 0-60°C | | | X | X | |
| 0-50°C | | X | X | X | X |
| 100-400°C | | | | X | |
| 100-500°C | | | X | X | X |

Dual Ranges, °F/°C

| Models | A | B ADJ | E J ADJ | G GJ ADJ |
|-----------------------|------|----------|---------------|----------------|
| Dial Size | 1.5" | 2.25" | 3" | 5" |
| -150-700°F -100-370°C | | | X | |
| -100-400°F -70-200°C | | X | X | |
| -90-130°F -68-55°C | | | X | |
| 0-130°F -15-50°C | | X | X | |
| 0-220°F -10-100°C | X | | | |
| 14-230°F -10-110°C | | X | X | X |
| 50-160°F 10-70°C | | | X | |
| 50-300°F 10-150°C | | X | | X |
| 50-550°F 0-300°C | X | | | |
| 50-500°F 10-260°C | | X | X | X |
| 150-750°F 65-400°C | | X | X | X |
| 200-1000°F 100-530°C | | | X | |